

Escape Sign Luminaire Profile 5004 CG-S





- Safety luminaire with rounded enclosure outline and clear cover made of plastic. Single-sided pictogram.
- Additional glass clear light emission with prismatic light control downwards
- Shortened inspection effort due to CEWA GUARD technology
- Automatic function monitoring of up to 20 luminaires per circuit
- Reduced installation expenditure with STAR technology
- Freely programmable mixed operation of the switching modes per luminaire in one circuit



5004 CG-S

Viewing distance	17 m
Luminous flux Φ_E/Φ_N at the end of rated operating time	75 %
Housing material	Plastic
Weight incl. cover	0.5 kg
Housing colour	White
Type of mounting	Wall mounting
Connection terminals	Loop terminals 2 x 2.5 mm ²
Connection voltage	220 – 240 V AC, 50/60 Hz 176 – 275 V DC
Current consumption with battery operation	20 mA
Power consumption mains operation	8 VA
Permissible ambient temperature	-10 °C to +40 °C
Light source	4 W/T16

Dimensions in mm



Ordering details

Type	Scope of supply	Order No.
5004 CG-S	Luminaire with CEWA GUARD monitoring and 20-digit address switch, without cover	4 0071 341 894
Cover PL acc. to DIN 4844	Cover with pictogram, silk screened	4 0071 349 618
Cover PR acc. to DIN 4844	Cover with pictogram, silk screened	4 0071 349 619
Cover PU acc. to DIN 4844	Cover with pictogram, silk screened	4 0071 349 620
Cover PL	Cover with pictogram, silk screened	4 0071 345 440
Cover PR	Cover with pictogram, silk screened	4 0071 345 441
Cover PU	Cover with pictogram, silk screened	4 0071 345 442

Accessories

Type	Order No.
Wire guard	400 71 348 370