

CG-Controller PC-Interface

Central Visualisation



CGLine PC-Interface
with integrated webserver

- Mail client for up to 10 mail recipients
- Up to 8 CGLine PC interfaces with up to 3,200 CGLine luminaires on CGVision possible
- Automatic luminaire search function (no manual addressing needed)
- Automatic function test, testing distance can be freely selected
- Automatic operating duration test, testing distance can be freely selected
- Blocking of emergency lighting function (complete or by bus line)
- Luminaires in maintained mode can be switched to OFF (to non-maintained light, complete or each line)
- Free input of luminaire target destination names, each with 20 characters and abbreviated address assignment via keyboard or by user-friendly PC software
- Password protection
- Removable configuration and test book memory via memory card for a period of at least 4 years
- Evaluation of the test book on memory card using optional card reader and CEAG software on a standard PC

Supply voltage (typ.)	230 V AC
Power consumption	< 4 Watt
Connection terminals	max. 2.5 mm ²
Permissible ambient temperature	0 °C ... 35 °C
Storage temperature	-20°C ... 70°C
Protection rate	IP 20
Housing	DIN-rail 10 TE
Dimensions	175 x 126 x 60 mm

Ordering details

Type	Scope of supply	Order No.
CGLine PC-Interface	PC-Interface connection box for wall mounting for DIN-rail	4 0071 360 020
SD-memory card (spare card)	SD-Card formatted for CG-Controller CGLine 400	4 0071 347 872
SD-card reader	SD-Card Reader for USB port	4 0064 070 561
Software	PC-Software for CGLine 400, for alternative configuration and log book evaluation on the PC	4 0071 347 535

